

CRUSE 3D Photostation



The new "all in one" 3D-System

High degree of automation and flexibility for the creation of 3D visualizations. Create 3D models, premium packshots, and 360° product animations in one single operation with the 3D Photostation

Cruse Digital North America Corp.

8080 Westpark Drive
Houston, Texas 77063, USA

Cel: +1 (713) 505-6843

Tel: +1 (713) 781-1856

Fax: +1 (713) 781-3443

E-Mail: sales@crusecamera.us

- + The 3D Photostation is instantly operational, without any sophisticated calibration procedures
- + Multilevel scanning of objects by means of automated swivel arm. Create 3D models of objects up to approx. 25 x 25 x 25 cm. (9.84" x 9.84" x 9.84")
- + LED light dome with more than 30 separately adjustable light channels and presets optimized for a large variety of objects and materials
- + Silent, smooth rotation in both directions
- + Diffused backlight for perfect cropping of objects
- + Fixed working distance between camera and projector provide for a high level of automation and perfect repeatability
- + Project templates and light presets for efficient handling of recurring tasks



Additional information: sales@crusecamera.us

www.crusecamera.us



Features

- + "All in one" system for packshots, 360° product animations and 3D models
- + Very easy handling, high degree of automation
- + Color management for print and web with device specific ICC profiles
- + Best reproducibility for 3D scanning and photography
- + High precision of 3D models (up to 100 µm)
- + High 2D image resolution, approx. 220 ppi in object plane, printable up to approx. DIN A3
- + Premium LED light
- + Various light presets optimized for different object and material characteristics
- + Excellent color accuracy for images and 3D textures
- + Spot and area illumination for any direction
- + CRUSE Image Manager integration

Technical specifications

Max. product size 3D	approx. 25 x 25 x 25 cm (9.84" x 9.84" x 9.84")
Max. original weight	approx. 25 kg (55 lbs.)
Lighting	pulsed LED light, approx. 5000 K
Projector	DLP, resolution 912 x 1140 pixel
File formats	stl, obj, tif, png
PC connection	Gigabyte Ethernet
Voltage	AC 100V - 240V
Dimensions	approx. 1,50 x 2,0 m (60" x 80")

Hardware and software requirements

OS	Windows 7/8/8.1/10 (64Bit)
Software	.NET Framework 4.0
CPU	Intel i7 (recommended)
RAM	at least 8 GB or more
HD	at least 100 GB free disc space
Graphic card	CUDA 3.0 compatible

Additional information: sales@crusescanner.us

www.crusescanner.us